



Retrofire DV

Dec 2022
1/1

Specifications

Product Codes	RF24JDN: natural gas / RF24JDP: propane
Product type	Direct Vent, Insert. Requires existing, unaltered, solid-fuel burning functioning fireplace/chimney.
Input (BTU)	Natural Gas: 20,000 / 6,500 Propane 18,000 / 12,500
Vent Outlet	REQUIRES a vent plate. RA24CL: Co-Linear AutoFire Vent Plate, 3x3 OR RA24CA: Co-Axial Flex Vent Plate, 3x5
Venting System	With RA24CL: Co-Linear 3x3, Roof termination. Optional wall termination w/720WSK. With RA24CA: Co-Axial Flex 3x5 with 590FVKV2 kit, Roof termination.
Gas convertible	Yes
Valve	GV60
Control	ValorPLUS remote control; optional Remote Battery & Wall Switch Kit or Wall Switch Kit
Batteries	Fireplace: Yes, in battery box; Remote control handset: Yes Optional Remote Battery & Wall Switch Kit
Electrical	Optional, to operate optional fan.
Lighting	No
Wifi	No
Fan (Blower)	¹ Optional. Operated by speed control box or hardwired with wall control. No remote.
HeatShift	No
Liners	No
Fuel beds	Logs: Traditional, Driftwood.
Fronts / Trims	No. Optional fret, yes.
Outdoor Installation	Yes, no electrical connection allowed. Requires GV60CKO Outdoor Conversion Kit.
Comments	¹ Fan operates independently from remote control.